

PATENT APPLICATION  
ATTORNEY DOCKET NO.: 041501-5452

UNITED STATES PATENT APPLICATION

OF

Jang Jin YOO

Do Hee KWON

and

Hyun Ho SHIN

FOR

LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME

09955979-092001  
T00260-62655660

[0001] This application claims the benefit of Korean Application No. P2000-55233 filed on September 20, 2000, which is hereby incorporated by reference.

## **BACKGROUND OF THE INVENTION**

### **Field of the Invention**

[0002] The present invention relates to a liquid crystal display (LCD) device, and more particularly, to a multi-domain LCD device that improves color characteristics and gray inversion regardless of a viewing angle.

### **Discussion of the Related Art**

[0003] In general, an LCD device includes lower and upper substrates. In the lower substrate, a plurality of pixel regions are arranged in a matrix shape, and each pixel region has a thin film transistor (TFT) and a pixel electrode. In the upper substrate, a common electrode and a color filter layer for representing colors are formed thereon. A liquid crystal is injected between the lower and upper substrates. A polarizer is respectively formed at both sides of the lower and upper substrates to linearly polarize visible rays.

[0004] Such LCD device is widely used in monitors for computers, audiocassette recorders, and videocassette recorders. The LCD

[0008] Operation of such LCD device is based on an electro-optical method, in which a voltage is applied to a liquid crystal cell to vary the alignment of the liquid crystal, thereby varying

electro-optical characteristics of the liquid crystal cell in representing images.

[0009] A viewing angle is an angle of eyes of a viewer with respect to the surface of the LCD device. Since a path of light passing through the liquid crystal layer varies with the angle of eyes of a viewer, birefringence of the liquid crystal is generated, thereby varying transmittance.

[0010] A viewing angle characteristic is a degree of the transmittance (contrast ratio) of the LCD device varying with the viewing angle.

[0011] Meanwhile, a related art lateral field induced vertical aligned (LFIVA) mode is a main stream technology in TFT-LCD devices. The LFIVA mode can achieve a wide viewing angle of 140 degrees or greater in any directions.

[0012] In such a mode, an alignment film on a common electrode is rubbed, and a pixel structure is formed in such a manner that a transparent electrode is etched in a portion of a pixel electrode at a width of 10  $\mu\text{m}$  to 15  $\mu\text{m}$  to form a slit pattern. Thus, electric fields are generated vertically and laterally. To the end, a wide viewing angle is obtained, so that a transmittance of 80%, a response time of 20 msec, and a viewing angle of 140 degrees or greater are achieved in the LFIVA mode.

[0018] FIG. 2 is a graph showing a relationship between a gray level and a viewing angle in the related art LFIVA mode LCD

**[0019]**As described above, the related art LFIVA mode LCD device has the following problems.

## SUMMARY OF THE INVENTION

**[0022]** Another object of the present invention is to provide an LCD device that improves color characteristic and gray inversion.

6

the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0024] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, an LCD device includes a first electrode on a first substrate having a plurality of slit patterns, a second electrode on a second substrate, a liquid crystal layer between the first and second substrates, the liquid crystal layer having different alignment directions by each slit pattern, and at least one light-shielding layer below the first electrode.

[0025] In another aspect of the present invention, a method of fabricating a liquid display device on first and second substrates includes forming at least one light-shielding layer on the first substrate, forming a first electrode having a plurality of slit patterns over the light-shielding layer including the first substrate, forming a second electrode on the second substrate, assembling the first and second substrates, and forming a liquid crystal layer having different alignment directions by each slit pattern between the first and second substrates.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0028] In the drawings:

**[0030]** FIG. 2 a graph showing a relationship between a viewing angle and a gray inversion in the related art LFIVA mode LCD device;

[0032] FIGs. 4A to 4E are graphs showing a transmittance of each gray level according to a black matrix width in the LCD device of the present invention;



[0033] FIG. 5 is a cross-sectional view showing a structure of the LCD device according to a second embodiment of the present invention;

[0034] FIG. 6 is a cross-sectional view showing a structure of the LCD device according to a third embodiment of the present invention; and

[0035] FIGs. 7A to 7E are chromaticity coordinates showing color characteristics according to the black matrix width of the present invention.

**DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS**

[0036] Reference will now be made in detail to the illustrated embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0037] FIG. 3 is a cross-sectional view showing a structure of an LCD device according to a first embodiment of the present invention.

*at A1* [0038] As shown in FIG. 3, the LCD device of the present invention includes first and second transparent substrates (both not shown) opposing each other and a first transparent electrode 22 having a plurality of slit patterns 21 at a constant distance on the first

substrate. The slit patterns 21 in the present invention are shown as a discontinuity in the pixel electrode (or the first transparent electrode 22). A second transparent electrode 23 is formed on the second transparent substrate opposing the first transparent electrode 22. Liquid crystals 24 are aligned to oppose each other by the slit patterns 21 between the first and second transparent electrodes 22 and 23. A black matrix (light-shielding layer) 25 is located below the first transparent electrode 22 at the center of the first substrate.

[0039] In fabricating processes, the black matrix 25 is formed on the first transparent substrate at a constant width, in the range of about 0  $\mu\text{m}$  to 8  $\mu\text{m}$ , for example. Then, an insulating film 26 is formed on the entire surface of the first transparent substrate including the black matrix 25. Subsequently, the first transparent electrode 22 having the slit patterns 21 is formed on the insulating film 26.

[0040] FIGs. 4A to 4E are graphs showing a transmittance of each gray level according to a black matrix width in the LCD device of the present invention.

[0041] As shown in FIGs. 4A to 4E, an electro-optical characteristic is improved with an increase in the width of the black matrix.

[0042] FIGS. 4A to 4E show the transmittance of each gray level when the width of the black matrix is respectively about 0  $\mu\text{m}$ , 2  $\mu\text{m}$ , 4  $\mu\text{m}$ , 6  $\mu\text{m}$ , and 8  $\mu\text{m}$ . As shown in FIG. 4E, the black matrix having a width of about 8  $\mu\text{m}$  has the best electro-optical characteristic among them.

[0043] FIG. 5 is a cross-sectional view showing a structure of the LCD device according to a second embodiment of the present invention.

000260-092001  
00055079-092001  
[0044] As shown in FIG. 5, the LCD device according to the second embodiment of the present invention includes first and second substrates (not shown) opposing each other and a first transparent electrode 22 having slit patterns at a constant distance on the first substrate. A second transparent electrode 23 is formed on the second substrate opposing the first transparent electrode 22. Liquid crystals 24 are aligned to oppose each other by the slit patterns 21 between the first and second transparent electrodes 22 and 23. A black matrix 25 is formed below the slit patterns 21.

[0045] In fabricating processes, the black matrix 25 is formed on the first substrate at a constant width. An insulating film 26 is then formed on the entire surface of the first substrate including the black matrix. Thereafter, the first transparent

electrode 22 having the slit patterns 21 is formed on the insulating film 26.

[0046] FIG. 6 is a cross-sectional view showing a structure of the LCD device according to a third embodiment of the present invention.

*Sub A3*  
100260-62655660  
[0047] As shown in FIG. 6, the LCD device according to the third embodiment of the present invention includes first and second substrates (not shown) and a first transparent electrode 22 having slit patterns 21 at a constant distance on the first substrate. A second transparent electrode 23 is formed on the second substrate opposing the first transparent electrode 22. Liquid crystals 24 are aligned to oppose each other by the slit patterns 21 between the first and second transparent electrodes 22 and 23. A black matrix 25 is formed below the first transparent electrode 22 and below the slit patterns 21 to shield lights.

[0048] At this time, the black matrix 25 is formed on the first substrate at a constant width. An insulating film 26 is formed on the entire surface of the first substrate including the black matrix 25.

[0049] Referring to FIGs. 7A to 7E, detailed descriptions as to variations of color characteristics will be discussed in accordance with the black matrix.

[0050] FIGs. 7A to 7E are chromaticity coordinates showing color characteristics according to widths of the black matrix. As shown in FIGs. 7A to 7E, as the width of the black matrix increases (from 0  $\mu\text{m}$  to 8  $\mu\text{m}$ ), the color characteristic is substantially improved at 0 degree (at left and right sides).

[0051] As aforementioned, the LCD device of the present invention has the following advantages.

[0052] A black matrix may be formed below the first transparent electrode having slit patterns. Alternatively, it can be located below the slit patterns or below both the first transparent electrode and the slit patterns. Thus, the dependency of the viewing angle in chromaticity coordinates is reduced. Furthermore, the inversion between gray levels can be reduced at right and left sides. Therefore, the gray inversion characteristic is improved.

[0053] It will be apparent to those skilled in the art that various modifications and variations can be made in the liquid crystal display (LCD) device and the method of fabricating the same of the present invention without departing from the spirit

or scope of the inventions. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

0955979-092001-62655660